

D85 Round Bale Stacker

ROUND BALE STACKER

The robust D85 Round Bale Stacker facilitates stacking bales on their flat side. This helps round silage bales keep their shape better.

The D85 Round Bale Stacker is ideal for handling bales from bale wrappers with end tip ramps. The sturdy, well-designed stacker arms ensure a full, secure and consistent grip at all times. A double-acting hydraulic ram ensures a tight hold which prevents damage to the plastic wrapping, while the stacker arms shape perfectly with the round sides of the bale. The stacker arms can be locked on one side and can comfortably manoeuvre between two closely stacked bales.

The D85 Round Bale Stacker is designed to handle round bales up to 1.5m in diameter.

CHARACTERISTICS

- Strong stacker arms shaped for close fit
- Double-acting ram for tight grip
- Ideal for bale wrappers with end tip ramps
- Handles up to 1.5m round bales
- Brackets available for all modern tractors & loaders



D80 Bale Stacker

TECHNICAL DATA IMPLEMENTS

SQUARE BALE STACKER

The D80 Bale Stacker allows for secure, safe and consistent handling of all sizes of large square and round bales. Simple in design but very effective in operation, this bale staker is the complete solution for the safe and damage-free handling of silage bales.

Two double-acting hydraulic ram ensures a full and consistent grip for all sizes of bales, which prevents damage to the plastic wrapping. Each arm can be locked in place with a tap to allow for easy stacking of bales. The design of the staker gives excellent operator vision of the bale at all times.

CHARACTERISTICS

- Stacks all sizes of large square and round bales
- Opening width of 2.1m and seal width of 0.6m
- Two Double-acting hydraulic ram for a tight grip
- Arm locking for easy bale stacking
- Interfaces bolted for telescopic or frontloader
- Maximum weight 1,500kg
- Pushpull two hydraulic connections (1/2")
- Requires a minimum of 150 bar pressure and 20 litres of oil
- Dimensions: 2.3m x 1.5m x 0.6m and 390kg



MODEL	173 Feeding	175 Feeding	D80 Handling	D85 Handling	160 CLEANFEED Feeding
TRANSPORT					
Height	-	-	0.62 m	0.66 m	1 m
Height (Closed)	0.85 m	0.9 m	-	-	-
Height (Open)	1.75 m	1.8 m	-	-	-
Width	1.82 m	2.0 m	2.10 m	-	2.50 m
Width (Closed)	-	-	-	1.45 m	-
Width (Open)	-	-	-	1.67 m	-
Length	1.10 m	1.30 m	1.50 m	-	1.60 m
Length (Closed)	-	-	-	1.44 m	-
Length (Open)	-	-	-	1.42 m	-
Weight	450 kg	630 kg	390 kg	200 kg	500 kg
BALE SIZES					
Max. Bale Length	1.20 m	1.40 m	2.00 m	1.30 m	-
Min. Bale Length	-	-	0.60 m	-	-
Max. Bale Diameter	1.55 m	1.55 m	-	1.50 m	-
Max. Bale Weight	1,400 kg	1,400 kg capacity	1,500 kg	1,400 kg	600 kg capacity
OPERATION					
Hydraulic Connection	Double acting service				Double & single acting service
Oil Pressure	210 bar / 150 bar				-
Oil Amount (Max / Min)	70 L / 20 L				75 / 35 L
Max. Counter Pressure	15 bar				