

CLEANAFEED

The 160 CleanaFeed is a low maintenance, self-loading, durable feeding implement for cleaning, washing and chopping root crops. Linkage (includes hydraulic top link) of front loader mounted option.

A rotor paddle removes loose dirt through an open framework and ensures even feed of crops to the chopper unit. The wash bar mechanism can be fitted to a water supply and has a low water requirement. The CleanaFeed is hydraulically driven and comes with an anti-bridging device and a simple hinged stone trap as standard. Optional attachment plates enable feeding of potatoes, vegetables, maize, grains and other feed compounds.

CHARACTERISTICS

- Linkage operated
- Self-loading
- Washes, cleans, chops and feeds
- Wash bar mechanism connects to water supply
- Anti-bridging device
- Stone trap
- Feed compound attachment plates - optional
- Brackets available for all modern tractors & loaders

TECHNICAL DATA IMPLEMENTS



MODEL	<i>I73</i> Feeding	<i>I75</i> Feeding	<i>D80</i> Handling	<i>D85</i> Handling	<i>I60 CLEANFEED</i> Feeding
TRANSPORT					
Height	-	-	0.62 m	0.66 m	1 m
Height (Closed)	0.85 m	0.9 m	-	-	-
Height (Open)	1.75 m	1.8 m	-	-	-
Width	1.82 m	2.0 m	2.10 m	-	2.50 m
Width (Closed)	-	-	-	1.45 m	-
Width (Open)	-	-	-	1.67 m	-
Length	1.10 m	1.30 m	1.50 m	-	1.60 m
Length (Closed)	-	-	-	1.44 m	-
Length (Open)	-	-	-	1.42 m	-
Weight	450 kg	630 kg	390 kg	200 kg	500 kg
BALE SIZES					
Max. Bale Length	1.20 m	1.40 m	2.00 m	1.30 m	-
Min. Bale Length	-	-	0.60 m	-	-
Max. Bale Diameter	1.55 m	1.55 m	-	1.50 m	-
Max. Bale Weight	1,400 kg	1,400 kg capacity	1,500 kg	1,400 kg	600 kg capacity
OPERATION					
Hydraulic Connection	Double acting service				Double & single acting service
Oil Pressure	210 bar / 150 bar				-
Oil Amount (Max / Min)	70 L / 20 L				75 / 35 L
Max. Counter Pressure	15 bar				